



**12V//16V AGM
RACING POWERCELLS**

SEALED NON-SPILLABLE LEAD ACID BATTERIES AND ACCESSORIES

REAL POWER UNREAL PERFORMANCE

Check Out Our Entire Line of XS Power Performance and Racing Products at 4XSPower.COM



S375 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 800 CA : 190A RC : 25min.

L: 7.87"(200mm) W: 3.03"(77mm) H: 5.43"(138mm)

Weight: 12.24lbs (5.55kg)



S545 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 800 CA : 240A RC : 15min.

L: 6.97"(177.03mm) W: 3.38"(85.8mm) H: 5.14"(130.55mm)

Weight: 11.01lbs (5.0kg)



S680 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 1000 CA : 320A RC : 28min.

L: 7.13"(181mm) W: 3.03"(77mm) H: 6.57"(167mm)

Weight: 15.42lbs (7.0kg)



S925 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 2000 CA : 550A RC : 55min.

L: 6.5"(165.1mm) W: 6.93"(176.02mm) H: 4.92"(124.96mm)

Weight: 23.54lbs (10.7kg)



S975 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 2100 CA : 525A RC : 50min.

L: 7.83"(198.88mm) W: 5.3"(134.62mm) H: 6.67"(169.42mm)

Weight: 26.43lbs (12kg)



S1200 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 2600 CA : 725A RC : 80min.

L: 7.8"(198.1mm) W: 6.54"(166.1mm) H: 6.69"(169.92mm)

Weight: 33.26lbs (15.1kg)

BILLET AND STAMPED ALUMINUM HOLD DOWNS

Check Out The Entire Line of Corrosion Resistant, XS Power Billet and Stamped Aluminum Hold Downs at 4XSPower.COM



535

*NHRA APPROVED

975 billet aluminum hold down



573

*NHRA APPROVED

3400/1400/1600 billet aluminum hold down



514

545 series stamped aluminum side mount box without window



527

S925 stamped aluminum GM direct mount and universal mounting kit

12V / 14V / 16V AGM RACING POWER CELLS



S3400 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 3300 CA : 1000A RC : 135min.

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.20"(182.88mm)

Weight: 46.0lbs (20.85kg)



A3400 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 3300 CA : 1000A RC : 135min.

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.20"(182.88mm)

Weight: 46.0lbs (20.85kg)



V3400 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 3300 CA : 1000A RC : 135min.

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.20"(182.88mm)

Weight: 46.0lbs (20.85kg)



S1600 / 16V AGM

16 Volt High Performance AGM Power Cell

MAX AMP : 2000 CA : 500A RC : 50min.

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.2"(182.87mm)

Weight: 30.5lbs (13.9kg)



XP 1000 / 16V AGM

16 Volt High Performance AGM Power Cell

MAX AMP : 2400 CA : 675A

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.2"(182.87mm)

Weight: 46.5lbs (21.1kg)



D1600 / 16V AGM

16 Volt High Performance AGM Power Cell

MAX AMP : 2400 CA : 675A RC : 85min.

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.2"(182.87mm)

Weight: 48.18lbs (21.85kg)



D1400 / 14V AGM

14 Volt High Performance AGM Power Cell

MAX AMP : 2400 CA : 675A Ah : 50

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.20"(182.87mm)

Weight: 43.56lbs (19.75kg)

TAKE CONTROL OF YOUR CHARGING SYSTEM



VCM / Voltage Control Module

Precision Charging for 12V, 14V and 16V

Digital Dash-Mount Control

Backlit Bright/Dim Display

Plug & Play Installation

GENUINE XS POWER CHARGERS AND ACCESSORIES



HF1615 *240V models available upon request
Compact High Frequency AGM IntelliCHARGER
15AMP Max Output. 12V, 14V and 16V Models Available



1004
16V AGM IntelliCHARGER - 20AMP Max Output



1005 *1005E model not shown, is 110V & 240V switchable
12V, 14V and 16V AGM IntelliCHARGER, Compatible 5A, 15A and 25A (25AMP Max Output), Three Charging Modes



PSC IntelliSUPPLY *15A, 30A and 60A Models Available
12V, 14V and 16V Compact High Frequency IntelliSUPPLY with AGM charge mode. 30A & 60A Models are 110V/240V compatible.



551
I-Bar Kit, Side and Top Terminal Adaptors



993
Compact Voltage Step-Down Module - 25AMP
Continuous, 50AMP MAX Output



Kit Contents

- 1qty - 16ft 2AWG XP FLEX RD Power Cable
- 1qty - 3ft 2AWG XP FLEX BK Ground Cable
- 8qty - XS Power Brand Heat Shrink
- 8qty - 2AWG Crimp Terminals
- 2qty - Battery Clamps
- 2qty - Grommets
- 10qty - Wire Clamps
- 10qty - Self Tapping Screws



RK2GA-1
XP FLEX, 2AWG, Single Battery, Light-Weight Racing
Battery Relocation Wiring Kit



Kit Contents

- 1qty - 22ft 2AWG XP FLEX RD Power Cable
- 1qty - 6ft 2AWG XP FLEX BK Ground Cable
- 14qty - XS Power Brand Heat Shrink
- 14qty - 2AWG Crimp Terminals
- 4qty - Battery Clamps
- 4qty - Grommets
- 14qty - Wire Clamps
- 14qty - Self Tapping Screws



RK2GA-2
XP FLEX, 2AWG, Dual Battery, Light-Weight Racing
Battery Relocation Wiring Kit

Distributed by:



XSPowerBATTERIES.COM • 888.4XSPower
2847 John Deere Dr. #102 Knoxville, TN 37917

Please note that product specs are subject to change. For the most up-to-date information regarding any XS Power Batteries product, please refer to xspowerbatteries.com