



**REAL POWER
UNREAL PERFORMANCE**
XSPowerBatteries.com

2012 RACING & PERFORMANCE

REAL POWER UNREAL PERFORMANCE

Check Out Our Entire Line of XS Power Performance and Racing Products at 4XSPower.COM



S375 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 800 CA : 190A RC : 25min.

L: 7.87"(200mm) W: 3.03"(77mm) H: 5.43"(139mm)

Weight: 12.24lbs (5.55kg)



S545 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 800 CA : 240A RC : 25min.

L: 6.97"(177.03mm) W: 3.38"(85.8mm) H: 5.14"(130.55mm)

Weight: 11.01lbs (5.0kg)



S680 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 1000 CA : 320A RC : 28min.

L: 7.13"(181mm) W: 3.03"(77mm) H: 6.57"(167mm)

Weight: 15.42lbs (7.0kg)



S925 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 2000 CA : 550A RC : 55min.

L: 6.5"(165.1mm) W: 6.93"(176.02mm) H: 4.92"(124.96mm)

Weight: 23.54lbs (10.7kg)



S975 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 2100 CA : 525A RC : 50min.

L: 7.83"(198.88mm) W: 5.3"(134.62mm) H: 6.67"(169.42mm)

Weight: 26.43lbs (12kg)



S1200 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 2600 CA : 725A RC : 80min.

L: 7.8"(198.1mm) W: 6.54"(166.1mm) H: 6.69"(169.92mm)

Weight: 33.26lbs (15.1kg)

BILLET AND STAMPED ALUMINUM HOLD DOWNS

Check Out The Entire Line of Corrosion Resistant, XS Power Billet and Stamped Aluminum Hold Downs at 4XSPower.COM



535

* NHRA APPROVED

975 billet aluminum hold down



573

* NHRA APPROVED

3400/1400/1600 billet aluminum hold down



514

545 series stamped aluminum side mount box without window



527

S925 stamped aluminum GM direct mount and universal mounting kit

12V / 14V / 16V AGM RACING POWER CELLS



S3400 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 3300 CA : 1000A RC : 135min.

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.2"(182.87mm)
Weight: 46.0lbs (20.85kg)



S1600 / 16V AGM

16 Volt High Performance AGM Power Cell

MAX AMP : 2000 CA : 500A RC : 50min.

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.2"(182.87mm)
Weight: 30.5lbs (13.9kg)



XP1000 / 16V AGM

16 Volt High Performance AGM Power Cell

MAX AMP : 2400 CA : 675A

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.2"(182.87mm)
Weight: 46.5lbs (21.1kg)



S1400 / 14V AGM

14 Volt High Performance AGM Power Cell

MAX AMP : 2000 CA : 500A RC : 50min.

L: 10.24"(260.1mm) W: 6.75"(171.4mm) H: 7.2"(182.87mm)
Weight: 28lbs (12.8kg)

TAKE CONTROL OF YOUR CHARGING SYSTEM



VCM / Voltage Control Module

Precision Charging for 12V, 14V and 16V
Digital Dash-Mount Control
Backlit Bright/Dim Display
Plug & Play Installation

WHY DID WE DESIGN A 14V BATTERY YOU ASK?

Because after years of studying and listening to the feedback from racers we realized that an intermediate step was needed between 12V and 16V batteries. We have found that there are many advantages the 14V battery offers to the racer who also drives their race car on the street. Since 14V batteries need to be charged at 16.8V, we have also introduced the all new **Voltage Control Module (VCM)** that very simply plugs into the factory or aftermarket alternator to allow it to charge at the appropriate voltage for the 14V battery. With a 16V battery, the alternator charge voltage would need to be 19.2V, which is too high for many of the sensitive electronics that may be present in a street and strip race car.

IT'S LIKE 16V FOR THE STREETS!

GENUINE XS POWER CHARGERS AND ACCESSORIES



1004
16V AGM IntelliCharger
Compatible 20 AMP Max Output
Dual Charging Modes



HF1615
16V High Frequency AGM IntelliCharger
Compact 15 AMP Max Output
12V, 14V & 16V Models Available



1005
12V and 16V AGM IntelliCharger
Compatible 5A, 15A & 25A (25AMP Max Output)
Three Charging Modes



586
Tall Automotive Brass Post Adapters
Compatible with all battery models.



551
I-Bar Side and Top Terminal Adapter



587
M6 to 3/8" Hardened Steel Stud Adapters
Compatible with all battery models.



XP FLEX

- Blue 1/0 (XPFLEX0BL-50)
- Black 1/0 (XPFLEX0BK-50)
- Red 1/0 (XPFLEX0RD-50)

- Blue 4 AWG (XPFLEX4BL-100)
- Black 4 AWG (XPFLEX4BK-100)
- Red 4 AWG (XPFLEX4RD-100)

XP Flex / True AWG 10% Oxygen Free Copper Clad (CCA)
STRAND CT : 5,250 MATL : 10% OXYGEN FREE CCA

XS Power is also proud to announce the release of our **XP Flex** line of cable. **XP Flex** is the Copper Clad Aluminum option in the power cable line, which offers extreme performance, light weight and high durability. However, if 100% Pure Oxygen Free Tinned Copper Cable with a massive 4,704 strand count is what you need, it is available in our **XS Flex** cable. The **XP Flex** cable is available in **Black (XPFLEX0BK-50)**, **Blue (XPFLEX0BL-50)** and **Red (XPFLEX0RD-50)** in both 50' spools or in 1' increments. The **XP Flex** cable is 10% Oxygen Free Copper Clad Aluminum (CCA) Cable with an oversized 5,250 strand count, which also exceeds the industry CEA-2015 cabling standards and is True AWG cable. The **XP Flex** cable is also designed to be super flexible and easy to use in any installation. All three **XP Flex** cables are also available in an oversized 2,009 strand count 4 AWG.

Distributed by:



888.4XSPOWER
2847 John Deere Dr. #102
Knoxville, TN 37917